



Sales / Technical Support: +1-818-338-7788 Option 3
 Email: sales@autecpower.com

DT-M036A Medical Application Series

Meet CEC, DoE Level VI, Energy Star, ErP Stage 2
 No Load Power Consumption Less Than 0.075W



Features :

- ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 edition 3.1)
- EMC : IEC60601-1-2 : 2014 (edition 4.0)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current: < 100µA
- 100-240VAC Universal Input
- Single Output to 36W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 2 Years Warranty

Desktop Medical Power Supply

Model	Output Voltage	Output Current	Power
DT-M036A-050-X-XX	5.0V	5.00A	25.00W
DT-M036A-075-X-XX	7.5V	4.00A	30.00W
DT-M036A-090-X-XX	9.0V	4.00A	36.00w
DT-M036A-120-X-XX	12.0V	3.00A	36.00W
DT-M036A-150-X-XX	15.0V	2.40A	36.00W
DT-M036A-180-X-XX	18.0V	2.00A	36.00W
DT-M036A-240-X-XX	24.0V	1.50A	36.00W

Available input plug options are:

U = C8, W = C6, V=C14, S=C18

